

provided within 200 feet (61 m) of such work areas.

[48 FR 30909, July 5, 1983, as amended at 62 FR 40197, July 25, 1997]

§ 1917.27 Personnel.

(a) *Qualifications of machinery operators.* (1) Only those employees determined by the employer to be competent by reason of training or experience, and who understand the signs, notices and operating instructions and are familiar with the signal code in use shall be permitted to operate a crane, winch or other power operated cargo handling apparatus, or any power operated vehicle, or give signals to the operator of any hoisting apparatus. *Exception:* Employees being trained and supervised by a designated person may operate such machinery and give signals to operators during training.

(2) No employee known to have defective uncorrected eyesight or hearing, or to be suffering from heart disease, epilepsy, or similar ailments that may suddenly incapacitate the employee, shall be permitted to operate a crane, winch or other power-operated cargo handling apparatus or a power-operated vehicle.

NOTE TO PARAGRAPH (A)(2): OSHA is defining suddenly incapacitating medical ailments consistent with the Americans with Disabilities Act (ADA), 42 U.S.C. 12101 (1990). Therefore, employers who act in accordance with the employment provisions (Title I) of the ADA (42 U.S.C. 12111-12117), the regulations implementing Title I (29 CFR part 1630), and the Technical Assistance Manual for Title I issued by the Equal Employment Opportunity Commission (Publication number: EEOC-M1A), will be considered as being in compliance with this paragraph.

(b) *Supervisory accident prevention proficiency.* (1) After October 3, 1985 immediate supervisors of cargo-handling operations of more than five (5) persons shall satisfactorily complete a course in accident prevention. Employees newly assigned to supervisory duties after that date shall be required to meet the provisions of this paragraph within ninety (90) days of such assignment.

(2) The course shall consist of instruction suited to the particular operations involved.³

[48 FR 30909, July 5, 1983, as amended at 62 FR 40197, July 25, 1997]

§ 1917.28 Hazard communication (See also § 1917.1(a)(2)(vi)).

§ 1917.29 Retention of DOT markings, placards and labels.

(a) Any employer who receives a package of hazardous material which is required to be marked, labeled or placarded in accordance with the U. S. Department of Transportation's Hazardous Materials Regulations (49 CFR parts 171 through 180) shall retain those markings, labels and placards on the package until the packaging is sufficiently cleaned of residue and purged of vapors to remove any potential hazards.

(b) Any employer who receives a freight container, rail freight car, motor vehicle, or transport vehicle that is required to be marked or placarded in accordance with the Hazardous Materials Regulations shall retain those markings and placards on the freight container, rail freight car, motor vehicle or transport vehicle until the hazardous materials which require the marking or placarding are sufficiently removed to prevent any potential hazards.

(c) Markings, placards and labels shall be maintained in a manner that ensures that they are readily visible.

(d) For non-bulk packages which will not be reshipped, the provisions of this section are met if a label or other acceptable marking is affixed in accordance with the Hazard Communication Standard (29 CFR 1910.1200).

(e) For the purposes of this section, the term "hazardous material" and any other terms not defined in this section have the same definition as in the

³The following are recommended topics: (i) Safety responsibility and authority; (ii) elements of accident prevention; (iii) attitudes, leadership and motivation; (iv) hazards of longshoring, including peculiar local circumstances; (v) hazard identification and elimination; (vi) applicable regulations; and (vii) accident investigations.